(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 24 February 2005 (24.02.2005)

(10) International Publication Number WO 2005/017627 A1

- (51) International Patent Classification7: G03F 7/42, 7/075
- (21) International Application Number:

PCT/US2003/023601

- (22) International Filing Date: 28 July 2003 (28.07.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:

US

09/789,083 (CIP)

Filed on

20 February 2001 (20.02.2001)

- (71) Applicant (for all designated States except US): DOW CORNING CORPORATION [US/US]; 2200 West Salzburg Road, Midland, MI 48686-0994 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): BECKER, Gregory [US/US]; 3347 Douglas Drive, Sanford, MI 48657 (US). GARDNER, Geoffrey [US/US]; 5042 North Fox Road. Sanford, MI 48657 (US). HARKNESS, Brian [US/US]: 5411 Wanetah Drive, Midland, MI 48640 (US).
- (74) Common Representative: DOW CORNING CORPO-RATION; 2200 West Salzburg Road, Midland, MI 48686-0994 (US).

- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR ETCHING A PATTERNED SILICONE LAYYER

(57) Abstract: A method for reworking semiconductor materials includes: (i) applying a silicone composition to a surface of a substrate to form a film, (ii) exposing a portion of the film to radiation to produce a partially exposed film having non-exposed regions covering a portion of the surface and exposed regions covering the remainder of the surface; (iii) heating the partially exposed film for an amount of time such that the exposed regions are substantially insoluble in a developing solvent and the non-exposed regions are soluble in the developing solvent; (iv) removing the nonexposed regions of the heated film with the developing solvent to form a patterned film; (v) heating the patterned film for an amount of time sufficient to form a cured silicone layer; and (vi) removing all or a portion of the cured silicone layer by exposure to an anhydrous etching solution including an organic solvent and a base.

